



EG 10 TILE GROUT

- 100% Stain Free
- Chemical Resistant
- Temperature Resistant
- Strong & Durable
- Anti Bacterial
- Anti Fungal

FOR WALL & FLOOR TILES
International Quality







AREAS OF APPLICATION:

To fill the joints between the tiled area where cleanliness is of utmost importance, wet areas like Kitchen, Bathroom, Swimming Pools, Public Toilets, Industrial Floorings, Hospitals, Parkings and High Trafficable areas.

HOW TO USE:

- Clean the surface thoroughly with clean water after 24 hours of tile laying.
- Wipe off the water and make the surface dry.
- Fill the joints of tiles with the help of squeeze trowel.
- Clean the tiles with wet sponge soffly after 10 minutes.
- Allow to dry for another 5 to 6 hours before using it.

Head Office:

House Of Tilemate Solutions

(An ISO 9001:2015 Certified Company)

G-8 Rafel Tower, Saket Square, Palasia, Indore-452001 (M.P.)

Mfg. By

House of Tilemate Solutions

M.P. 452001 INDIA

For More Information, Visit Our Website: www.ecogrip.in For Feedback/Complaints,

Follow Us On: ecogrip tile (1) (a) (b)

Batch No.

Mfg. Date

MRP

(inclusive of all Taxes)

Net. Wt. **IKG**











SHELF LIFE: 12 months from the date of manufacture. Store unopened in normal& dry condition.